

Fiber Networking Solutions

RJSB fiber panel is sliding version with 1U height, it has been designed to accept from 12fibers up to 96 fibres . Our panels with various changeable faceplates available, customer can choose different faceplates according to their own needs,those faceplates are from 12 ports, 24 ports and 48 ports.

With the full range of the adaptor types, customer can easlily working on the panels during the installations or re-work with no distrubance of the existing cables.



Features

- . Up to 96 fibres in 1U
- . Multiple Adaptor options available
- . 24 PCS SC SIMPLEX / LC DUPLEX/LC QUAD
- . Recessed Adaptor positioning
- . Individually labelled ports
- . 45°Zopen working angle
- . Accepts loose tube, distribution and pre terminated cables . RoHS, REACH SvHC and UL rated
- . Fits standard 19"



Get in Touch

Email: sales@rjconnect.co.za | **Email:** info@rjconnect.co.za | **Tel:** +27 11 781 0777

Address: 1 Avocet Close, Bromhof, Johannesburg, South Africa, 2154

Fiber Networking Solutions

Applications

- . Data centres, premise installations, telecommunication networks
- . Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- . Data communication
- . Indoor applications

Specifications

U Size	1U (44.4mm)
Width	455mm
Depth	250mm
Net weight	2.5 kgs
Packaged weight	3 kgs
Packaged dimensions	530mm W X 55mm H x 260mm D
IP rating	IP20
Suitable for Adaptor type	SC、FC、ST、LC、E2000
Number of ports	24
Cable Entry 20mm	2
Cable entry 25mm	2
Mounting Adjustment range	50mm
Material thickness	1.2mm
Material coating	Powder coating
Colour	RAL 9004
Operating temperature	-40° C to +50° C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754
Compliant to	RoHS, Reach/SVHC

Get in Touch

Email: sales@rjconnect.co.za | **Email:** info@rjconnect.co.za | **Tel:** +27 11 781 0777

Address: 1 Avocet Close, Bromhof, Johannesburg, South Africa, 2154